

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



PCT


EP. 0029440  
WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>3</sup>: E05B 47/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 80/02710 (43) International Publication Date: 11 December 1980 (11.12.80)</p>
<p>(21) International Application Number: PCT/SE80/00155 (22) International Filing Date: 29 May 1980 (29.05.80) (31) Priority Application Number: 7904702-3 (32) Priority Date: 30 May 1979 (30.05.79) (33) Priority Country: SE  (71) Applicant (for all designated States except US): HANDELSBOLAGET ID-SELECT BO THELIN &amp; CO. [SE/SE]; Ekallén 2, S-230 44 Vintrie (SE). (72) Inventor, and (75) Inventor/Applicant (for US only): NORDSTRAND, Claes [SE/SE]; Gustav Adolfs Torg 8C, S-211 39 Malmö (SE). (74) Agents: WALLIN, John et al.; Awapatent AB, Box 5117, S-200 71 Malmö (SE).</p>		<p>(81) Designated States: AT (European patent), AU, BR, CH (European patent), DE (European patent), DK, FR (European patent), GB (European patent), JP, LU (European patent), NL (European patent), NO, US.  <b>Published</b> <i>With international search report Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: ELECTRONIC LOCK



(57) Abstract

An electronic lock comprising electronic circuits (4) for determining the identity of a presented key (2) and releasing an opening movement of a lock mechanism (3) is provided with a handle-operated electric generator (7) connected to a storage battery (6) for supplying current to the electronic circuits (4).

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	LI	Liechtenstein
AU	Australia	LU	Luxembourg
BR	Brazil	MC	Monaco
CF	Central African Republic	MG	Madagascar
CG	Congo	MW	Malawi
CH	Switzerland	NL	Netherlands
CM	Cameroon	NO	Norway
DE	Germany, Federal Republic of	RO	Romania
DK	Denmark	SE	Sweden
FR	France	SN	Senegal
GA	Gabon	SU	Soviet Union
GB	United Kingdom	TD	Chad
HU	Hungary	TG	Togo
JP	Japan	US	United States of America
KP	Democratic People's Republic of Korea		

ELECTRONIC LOCK

The present invention concerns an electronic lock.

For a number of reasons, electronic locks are preferred to entirely mechanical locks in many instances.

An electronic lock is a lock where electronic circuits  
5 are utilized for determining the identity of a presented key and for releasing an opening movement of essentially ordinary mechanical details, if the identity of the key is the correct one.

To be able to function, the electronic circuits of  
10 an electronic lock must be supplied with current, for which reason the lock has to be connected to the electric mains or to some kind of battery. In both cases, a supply current failure may prevent normal opening of the lock, and this is, of course, a serious disadvantage.

15 The present invention aims at providing an electronic lock in which the current supply is guaranteed in a simple manner.

To achieve this aim in an electronic lock of the type mentioned above, the lock is provided with a manually  
20 operable electric generator connected to an energy storage device adapted to supply the electronic circuits with the required current.

According to a preferred embodiment of the lock comprised by the present invention, the electric generator  
25 is operable by means of a handle for actuating the lock.

The invention will be described in more detail in the following, reference being had to the accompanying drawing in which:-

Fig. 1 is a block diagram of an electronic lock  
30 according to the invention;

Fig. 2 is a highly diagrammatic side view of an embodiment of an electric generator in a lock according to the invention.

The electronic lock illustrated in Fig. 1 comprises  
35 in known manner a lock member 1 which may be mounted in.



a door leaf, and a key member 2. The lock member 1 comprises a lock mechanism 3 which may be of any known construction whatsoever, and also a lock electronic system 4. The key member 2 contains information which identifies the key member 2 and can be transmitted, in some known manner, to electronic circuits provided in the lock electronic system 4 to be determined thereby as the correct information for opening the lock. In such cases, the lock mechanism 3 is actuated or released by the lock electronic system 4.

The lock electronic system 4 is supplied with current via lines 5 from a storage battery 6 which can be charged by means of a manually operable electric generator 7 via lines 8.

As has been shown diagrammatically in Fig. 2, the electric generator 7 may be equipped with a permanent magnet rotor 10 having alternating magnetic poles around its periphery and an iron yoke 11 on which a coil 12 is wound. The coil 12 is connected to the storage battery 6 via a rectifier 13.

The rotor 10 can be rotated clockwise by means of a push bar 15 which is guided between pins 14 and is articulated with a handle 16. When the handle is depressed, the push bar is displaced towards the rotor 10, and a spring 17 articulated with the push bar 15 will be compressed. At the end of the movement of the push bar 15 a cam surface 18 on the push bar causes such a rotation of the rotor 10 and the end of the spring 17 engaging a notch provided in the periphery of the rotor that the energy stored in the spring 15 by the compression thereof will be released and converted into a rotational movement of the rotor 10. During rotation of the rotor 10, an alternating voltage is induced in the coil 12 and, after rectification in the rectifier 13, charges the storage battery 6.

The handle 16 preferably is the one normally provided for manually actuating the lock mechanism 3 of the lock member.

It will be appreciated that the electric generator



and the manual operation thereof can be accomplished in many other ways than that described above; for example, the generator may be a piezoelectric generator. Those skilled in the art will also realise that any other energy storage device, such as a capacitor, may be substituted for the storage battery 6.



## CLAIMS

1. An electronic lock comprising electronic circuits (4) for determining the identity of a presented key (2) and releasing an opening movement of a lock mechanism (3), characterized by a manually operable electric generator (7) which is connected to an energy storage device (6) adapted to supply current to the electronic circuits (4).

2. An electronic lock as claimed in claim 1, characterized in that the electric generator (7) is operable by means of a handle (16) adapted to actuate the lock mechanism (3).

3. An electronic lock as claimed in claim 2, characterized in that the electric generator (7) comprises a magnet (10) which is rotatable by means of the handle (16), a coil (12), and a rectifier (13).

4. An electronic lock as claimed in claim 1 or 2, characterized in that the electric generator (7) is a piezoelectric generator.





1/1

FIG. 1





FIG. 2



# INTERNATIONAL SEARCH REPORT

International Application No PCT/SE80/00155

## I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) \*

According to International Patent Classification (IPC) or to both National Classification and IPC 3

E 05 B 47/00

## II. FIELDS SEARCHED

Minimum Documentation Searched 4

Classification System

Classification Symbols

IPC 3

National Cl

US Cl

E 05 B 47/00-49/04; M 02 K 7/08

68a:38-42

70:271, 277-283, 434; 310:75; 292:144, 201

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in the Fields Searched 5

SE, NO, DK, FI classes as above

## III. DOCUMENTS CONSIDERED TO BE RELEVANT 14

Category *	Citation of Document, 14 with indication, where appropriate, of the relevant passages 17	Relevant to Claim No. 18
X	DE, A, 2 324 392 published 1974, December 5, Recognition Devices Inc	
X	US, -A, 1 365 814 published 1921, January 18, Bryce	
X	US, A, 971 690 published 1910, October 4, Schmidt	

\* Special categories of cited documents: 19

"A" document defining the general state of the art

"E" earlier document but published on or after the international  
filing date

"L" document cited for special reason other than those referred  
to in the other categories

"O" document referring to an oral disclosure, use, exhibition or  
other means

"P" document published prior to the international filing date but  
on or after the priority date claimed

"T" later document published on or after the international filing  
date or priority date and not in conflict with the application,  
but cited to understand the principle or theory underlying  
the invention

"X" document of particular relevance

## IV. CERTIFICATION

Date of the Actual Completion of the International Search \*

1980-09-30

Date of Mailing of this International Search Report \*

1980-10-01

International Searching Authority \*

Swedish Patent Office

Signature of Authorized Officer 20

Christer Wendenius